AQA drink Pure SLIM

Model UK	SLIM 2		
Filter Ø (F)	1/4 inch	**Flow Pressure**	1.7 – 2.7bar
Maximum Flow rate	3 L/min		
Capacity up to	- Magnesium resin cartridge 800-1200L(CaCO3 Hardness 9-12 °dH) - **High efficiency activated carbon cartridge** 4000L(Chlorine@2ppm)		
Maximum Temperature water /surrounding	30/40 ℃		
Dimensions	H405*W167*D110(mm)		



Model UK	SLIM 3		
Filter Ø (F)	1/4 inch	**Flow Pressure**	1.7 – 2.7bar
Maximum Flow rate	2 L/min		
Capacity up to	- **Magnesium resin cartridge 800-1200L(CaCO3 Hardness 9-12 °dH)** - **High efficiency activated carbon cartridge** 4000L(Chlorine@2ppm) - **Membrane Cartridge** 4000L		
Maximum Temperature water /surrounding	30/40 ℃		
Dimensions	H405*W167*D190(mm)		



Functions of SLIM Cartridges

Model	Features
SLIM-C High Efficiency Activated Carbon	NSF certified 5 micron PP outer layer removes impurities, suspended solids and micro-particles. An additional layer of activated carbon provides efficient removal of harmful pollutants, chemicals, insecticides, chlorine, odors, and heavy metals. At the center, a 1 micron PP filter serves as a final stage of filtration.
SLIM-UF Membrane multi-filter	NSF certified filters consisting of membranes ranging 0.1 µm in filtration diameter. The filters effectively remove 99.99% of bacteria and viruses while preserving desirable minerals; ensuring safe and healthy unboiled water.
SLIM-MG Magnesium ions exchange resin filter	Magnesium ion exchange filters adsorb limescale, calcium carbonate, and heavy metals. Through the process, magnesium ions are deposited in the water to develop a mildly alkaline nature, allowing for healthier, tastier water.

All information is given for guidance only and the final results will depend on local conditions - Please call us for advice

BWT UK Limited
Suite G, Artisan, Hillbottom Road,
High Wycombe, Buckinghamshire, HP12 4HJ